

Akuvox R15P brings high-quality, cost effective solution to the seniors. The intuitive user interface of the Akuvox R15P makes navigation easy and requires minimal training.

- Easy to use
- HD Voice with High Adjustable Volume
- Adjustable Tone
- Hearing Aid Compatible (HAC)
- Big Buttons, SOS key
- Up to 10 Wireless Emergency Pendants Supported(Optional)
- Support PoE
- Fully Compatible with Asterisk, BroadSoft Platform



### ■ Phone Features

- 1 Line (Support 1 SIP account)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Tone Adjustable
- Ring tones Selectable
- Speed Dial, Hotline
- Network Packet Capture
- Country Tone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- Action URL/URI
- Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)
- Multi-Language Support
- Health Care
- Remote mode switch

### ■ IP-PBX Features

- SMS, MWI
- Music on hold, Intercom
- Call Pickup, Group Call Pickup
- Call Recording
- Anonymous Call, Anonymous Call Rejection

### ■ Security Features

- Support HTTPS (SSL)
- Support SRTP for Voice Data Encryption
- Support Login for Administration
- SIP Over TLS

### ■ Audio Features

- HD Voice with high volume
- Hearing Aid Compatible (HAC)
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_16, G726\_24, G726\_32, G726\_40
- VAD, CNG, Echo Cancellor
- Full-Duplex Speakerphone

### ■ Operation

- When SOS button or pendant is pressed, three Emergency call numbers will be called out in a loop, and each emergency number will be tried for 3 times.
- When answer the emergency call, an preset emergency outgoing voice message will be played repeatly.
- The called side should press DTMF number 5 to confirm receiving the emergency call.

### ■ Network Features



- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP configuration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1Q VLAN

### ■ Administration Features

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Management with Web, Keypad on the phone and Auto Provisioning
- SNMP
- TR069

### ■ Physical Features

- Audiocodes Chipset
- 2.9" 132x64 Graphical LCD with Backlight
- 25 Keys (with 1 SOS key, 4 Soft Keys, 3 Image Programmable Keys)
- 3 LED Lights (1 Power Light, 1 Handfree Light and 1 SOS Light)
- Up to 10 Wireless Emergency Pendants Supported(Optional)
- RJ9 Handset Jack and Headset Jack
- 2 RJ45 10/100 Ethernet Jacks
- AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- PoE: IEEE 802.3af
- Gift Box Size:248 x 204 x 107 (mm),weight: 1.19 kg

R15 Model 	Pendant Model 	Working Range
R15P	NA	NA
R15P(433)	EP10(433)	Outdoor 250m/indoor 30m
R15P(869)	EP10(869)	To be confirmed

Note: 433 means 433MHz frequency, 869 means 869MHz frequency.